

Document Type	Code	Date	Version
Technical Data Sheet	Z-200/400.01	01.09.2022	01
	1		
Martarial Catagon	Matarial / Draduct Consision		

Material Category	Material	Material / Product Specification	
Plastic Netting	RU702	RU7020-200	
	Unit		
	OTTIL		
Number of needles per 1 inch	-	6	
Polymer	-	HDPE	
Colour	-	Anthracite gray	

Number of needles per i inch	_	O
Polymer	-	HDPE
Colour	_	Anthracite gray
UV Stability	-	Yes
Shading	%	65 – 70
Width	cm	200
Weight	g/m²	115
Strength - chain	N/m	519
Strength - weft	N/m	210
Flash Point	°C	330 - 350
Ignition Temperature	°C	440
Melting Point	°C	130

Comment

For and on behalf of Milmar, spol. s r.o.

- Highly flammable material (C-3 category)
- Almost zero absorbency
- High chemical resistance (most acids and bases even at elevated temperatures)
- Made of thermoplastic
- It must not be permanently exposed to temperatures higher than 70°C and intermittently 90°C.

Milan Polouček, Managing Director

The above data are based on the knowledge available at the time of printing and may be subjected to amendments due to changes of the methods of manufacturing. The figures are reported as typical values only and should therefore not be taken as a guarantee of performance. Milmar, spol. s r.o. reserves the right to improve the product and adjust the specification without any further notice.