

<i>Document Type</i>	<i>Code</i>	<i>Date</i>	<i>Version</i>
Technical Data Sheet	Z-200/424.01	01.09.2022	01

<i>Material Category</i>	<i>Material / Product Specification</i>
Plastic Netting	RU9020-150

	<i>Unit</i>	
<i>Number of needles per 1 inch</i>	-	3
<i>Polymer</i>	-	HDPE
<i>Colour</i>	-	Anthracite gray
<i>UV Stability</i>	-	Yes
<i>Shading</i>	%	85 – 90
<i>Width</i>	cm	150
<i>Weight</i>	g/m <sup>2</sup>	110
<i>Strength – chain</i>	N/m	-
<i>Strength – weft</i>	N/m	-
<i>Flash Point</i>	°C	330 – 350
<i>Ignition Temperature</i>	°C	440
<i>Melting Point</i>	°C	130

*Comment*

- *Highly flammable material (C-3 category)*
- *Almost zero absorbency*
- *High chemical resistance (most acids and bases even at elevated temperatures)*
- *Made of thermoplastic*
- *It must not be permanently exposed to temperatures higher than 70°C and intermittently 90°C.*

For and on behalf of Milmar, spol. s r.o.



Milan Polouček, Managing Director

*The above data are based on the knowledge available at the time of printing and may be subjected to amendments due to changes of the methods of manufacturing. The figures are reported as typical values only and should therefore not be taken as a guarantee of performance. Milmar, spol. s r.o. reserves the right to improve the product and adjust the specification without any further notice.*